

PD4STP

3" Surface-Mount Satellite Speaker for Subwoofer
Satellite Loudspeaker System (Pair)



PYLE
PyleUSA.com

USER GUIDE

INTRODUCTION

The mini satellite speakers are designed to be compact and discreet while delivering excellent sound quality. They are well suited for a wide variety of residential and commercial applications, including home entertainment, multi-room and conference room systems, retail outlets, and more.

Technical Specs:

- MAX Power: 30W
- RMS Power: 10W
- Impedance: 8 Ω
- Sensitivity(1M/1W): 90dB
- Frequency Response: 100Hz-20kHz
- Driver Type: 2.5" Paper cone full range speaker
- Cabinet Material: ABS
- Bracket Design: Ball-Joint full-motion plastic bracket
- Product Dimensions (L x W x H):
3.7 x 3.7 x 3.4 -inches

Questions? Issues?

We are here to help!

Phone: (1) 718-535-1800

Email: support@pyleusa.com

California Prop 65 Warning

⚠ WARNING:

This product contains Bisphenol A (BPA) which is known to the state of California to cause cancer birth defects and other reproductive harm. Do not ingest.

For more info go to: www.P65warnings.ca.gov

INSTALLATION



SPEAKER MOUNTING

If mounting the speakers, always utilize the included hardware. Please keep in mind that not all fastener types are included; use appropriate screws and/or wall anchors for your wall type. It is not recommended to install the speaker on unreinforced drywall or plasterboard. Once the wall bracket is mounted, then attach the speakers accordingly. If you are unsure of how or where to install the speaker, please consult a professional audio/video installer.

CONNECTING THE SPEAKER

Remove the green terminal adapter from the speaker and connect speaker wire to it before reinserting. Make sure the wires are connected in the correct polarity as marked on the back of the speaker: + is positive, - is negative. It is recommended to always use color-coded wires to ensure a correct connection between the amplifier and speakers.

