

PYLE®



view

AV SIGNAL CONVERTER
BY REMOTE CONTROL



PLVSC404

Operational Manual:

1. Connect Audio/Video source of DVD/VCD/TV Tuner to AV-IN connectors by RCA jacks. This system can operate up to four AV sources.
2. Connect AV-IN of monitors to AV-OUT on the converter system. This system can operate up to four monitors simultaneously.
3. Power supply by DC+12V. there are three wires:
Red wire: DC+12V
Black wire: Ground
Yellow wire: Control On/Off of the converter
4. Button (1), (2), (3), (4) on remote control represent signal output source selector of the converter.
5. Push button (1), monitor (1) will be connected then press again button (1), connection of AV-IN sources will be changed from (1) to (2) or (2) to (3) or (3) to (4) etc.
Keep pressing selector button on remote control will access to desired AV-IN sources.
These operating processes apply to the other monitors.

Features:

- 4 Audio/Video Inputs by RCA Jacks
- 4 Monitors Outputs by RCA Jacks.
- Remote IR Eye Port by Din socket
- Power Input: by 4- pin Plug - type Connector

Specifications:

- Video Input: Composite Video 1 Vpp 75 Ohm
- Audio Input: 0 ~1 Vpp, 20 ~20K Hz
- Video Output: Composite Video 1 Vpp 75 Ohm
- Audio Output : 0 ~ 1Vpp, 20 ~ 20K Hz
- Power Supply: DC 12V, +/- 10%, max. 200mA

Installation:

